

INTRODUCING A MINI-SPLIT WITH A FRESH AIR KIT OPTION



HIGH PERFORMANCE & EFFICIENCY WITH THE ADDED OPTION OF FRESH AIR INTO YOUR SPACE

CLIVIA systems can handle those challenging environments that require outside air when you include the optional fresh air kit. With GREE's superior reliability and performance, the CLIVIA can tackle most applications.

- OPTIONAL FRESH AIR KIT

- UP TO 26.0SEER2/
15.0 EER2 /
10.4 HSPF2 EFFICIENCY

- COOLING RANGE: -29°C to 50°C

- HEATING RANGE: -30°C to 30°C

- MAXIMUM LINE LENGTH: 40 m

- Option for Fresh Air kit
- Dehumidification
- Auto-Clean
- Self-diagnosis
- Multiple fan speeds

- Automatic voltage adaptation
- Swing louver control
- A2L leak detection sensor, included
- Built-in Wifi included



Product #	Indoor Unit		GWH09AUCXD-D6DNA2D/I	GWH12AUCXD-D6DNA2D/I	GWH18AUDXF-D6DNA2C/I	GWH24AUDXF-D6DNA2J/I
	Outdoor Unit		GWH09AGCXD-D6DNA4D/O	GWH12AGCXD-D6DNA4D/O	GWH18AGDXF-D6DNA4B/O	GWH24AGEXF-D6DNA4J/O
Technical Performance						
Voltage		Volts	208/230	208/230	208/230	208/230
Cooling capacity	Nominal	W (BTU/hr)	2667 (9100)	3517 (12000)	5275 (18000)	6450 (22000)
	Min. – max.	W (BTU/hr)	800 - 3800 (2730 -12966)	800 - 4600 (2730 - 15013)	1500 - 6500 (5118 - 22178)	1170 - 8000 (3990 - 27300)
Heating capacity	Nominal	W (BTU/hr)	3077 (10500)	3517 (12000)	5275 (18000)	6740 (23000)
	Min. – max.	W (BTU/hr)	700 – 4280 (2388 - 14600)	900 - 4280 (3070 - 14600)	1300 - 5660 (4436 - 19310)	850 - 7030 (2900 - 24000)
Used cooling power input	Nominal	W	606	923	1315	1833
	Min. – max.	W	190 - 1090	90 - 1450	130 - 2300	215 - 2850
Used heating power input	Nominal	W	789	923	1349	2040
	Min. – max.	W	150 - 1520	160 - 1400	230 - 2350	215 - 3800
Used rated input		W	1520	1450	2350	3800
Rated current		A	6	6.64	11.5	17
MCA		A	10	10	16	22
Max. over-current protection (MOCP)		A	15	15	20	30
SEER2		-	26.0	24.5	24.5	23.5
HSPF2		-	10.4	9.5	9.0	9.0
EER2		BTU/hr	15	13	13.65	12
EER		W/W	4.4	3.81	4.01	3.52
COP		W/W	3.90	3.81	3.91	3.30
AHRI number		-	216032435	216032436	216052270	216623541
ENERGY STAR		-	✓	✓	✓	✓
Indoor Unit						
Dehumidification		pt/hr (l/hr)	1.69 (0.8)	2.96 (1.4)	3.80 (1.8)	5.07 (2.4)
Air flow volume		cfm	353 / 324 / 294 / 265 / 235 / 206 / 194	400 / 365 / 330 / 288 / 265 / 247 / 230	589 / 500 / 441 / 412 / 383 / 353 / 324	559 / 441 / 394 / 353 / 312 / 253 / 235
Sound Pressure Level (H / M / L)		dB (A)	39 / 33 / 26	38 / 34 / 30	43 / 39 / 33	43 / 39 / 33
Fan motor power output		W	55	55	50	50
Fan motor RLA		A	0.35	0.40	0.60	0.70
Deflector stepper motor power output		W	1.5	1.5	1.5	1.5
Net weight		lb (kg)	20.9 (9.5)	20.9 (9.5)	29.8 (13.5)	29.8 (13.5)
Outdoor Unit						
Air flow volume		m3/hr	2200	2200	3600	3200
Sound Pressure Level		dB (A)	52	52	59	58
Compressor power input		W	800	857	1196	1330
Compressor LRA		A	25	18	22	35
Compressor RLA		A	6.5	7	10.35	15.3
Fan motor power output		W	30	30	60	60
Fan motor RLA		A	0.96	0.7	1.35	0.9
Refrigerant volume (R32)		oz (g)	30 (850)	28.2 (800)	40.6 (1150)	42.3 (1200)
Net weight		lb (kg)	70.6 (32)	67.3 (30.5)	94.8 (43)	92.6 (42)
Operating ambient temperature	Cooling	°C (°F)	-29-50 (-20-122)			
	Heating	°C (°F)	-30-30 (-22-86)			
Connection Piping/Refrigerant						
Pre-charge length		ft. (m)	24.6 (7.5)	24.6 (7.5)	24.6 (7.5)	24.6 (7.5)
Additional refrigerant charge		oz/ft. (g/m)	0.2 (16)	0.2 (16)	0.2 (16)	0.4 (40)
Liquid pipe outer diameter		in.	1/4	1/4	1/4	1/4
Gas pipe outer diameter		in.	3/8	1/2	1/2	5/8
Maximum height difference		ft. (m)	40 (12.2)	40 (12.2)	82 (25)	82 (25)
Maximum total length		ft. (m)	65 (19.81)	65.6 (20)	131.2 (40)	131.2 (40)

*10 year standard warranty. Additional 2 year extended warranty with Wolseley when product is registered and/or proof of installation.