

IT ALL FITS TOGETHER
FOR COMFORT



A MULTI-ZONE SYSTEM WITH ALL THE OPTIONS FOR EACH SPACE

GREE's Multi-Zone systems deliver versatility and high performance. With 7 indoor options to choose from, each space is optimally treated for comfort and efficiency.

- UP TO 21 SEER2/
12.5 EER2 /
10 HSPF2 EFFICIENCY
- COOLING RANGE: -30°C to 48°C
- HEATING RANGE: -30°C to 24°C
- MAXIMUM LINE LENGTH: 100 m

- Self-Diagnosis
- Indoor units powered by outdoor unit
- Intelligent defrost
- Automatic voltage adaptation
- Small footprint design
- Advanced G10 inverter technology
- Quiet operation
- Up to 7 unique indoor options
- A2L leak detection sensor, included

FREE MATCH R32



Eligible for
local rebates



Product #			GWHD(18)ND6MO	GWHD(24)ND6MO	GWHD(30)ND6MO	GWHD(36)ND6MO	GWHD(42)ND6MO
Technical Performance							
Number of connectable indoor unit		-	2	2 to 3	2 to 4	2 to 4	2 to 5
Voltage		Volts	208/230	208/230	208/230	208/230	208/230
Cooling capacity	Nominal	W (BTU/hr)	5275 (18000)	7030 (24000)	8300 (28400)	10550 (36000)	12310 (42000)
	Min. – max.	W (BTU/hr)	2140 – 5800 (7300 – 19800)	2200 – 9200 (7500 – 31400)	2400 – 10000 (8190 – 34100)	2600 – 12000 (8870 – 40900)	2600 – 13000 (8870 – 44300)
Heating capacity	Nominal	W (BTU/hr)	5275 (18000)	7030 (24000)	8800 (30000)	10550 (36000)	12310 (44300)
	Min. – max.	W (BTU/hr)	2140 – 5305 (7300 – 18100)	2200 – 9200 (7500 – 31400)	2400 – 12000 (8190 – 40900)	2600 – 15000 (8870 – 51180)	2600 – 16000 (8870 54590)
Used cooling power input	Nominal	W	1500	1850	2075	3000	3230
Used heating power input	Nominal	W	1350	1800	2100	2960	3150
MCA		A	14.5	19.5	23	30	30
Max. over-current protection (MOCP)		A	20	25	35	45	45
SEER2		-	21	21	21	21	21
HSPF2		-	10	10	10	10	10
EER2		BTU/hr	12.5	12	12.5	12	12
EER		W/W	3.52	3.8	4	3.52	3.81
COP		W/W	3.9	3.9	4.19	3.56	3.9
AHRI numbers	Non-Ducted	-	214931586	214931587	214931588	214931589	214931590
	Ducted	-	214931591	214931593	214931594	214931595	214931596
	Mixed	-	214931592	214931597	214931598	214931599	214931600
ENERGY STAR		-	✓	✓	✓	✓	✓
Air flow volume		cfm	1354	2236	3413	3413	3413
Sound pressure level (High)		dB (A)	54	58	62	63	63
Compressor power input		W	1300	1887	2047	3514	3514
Compressor LRA		A	-	-	-	-	-
Compressor RLA		A	9.5	12	13.5	19.6	19.6
Fan motor power output		W	30	60	130	130	130
Refrigerant volume (R32)		oz (g)	31.8 (900)	60 (1700)	77.6 (2200)	95.3 (2700)	95.3 (2700)
Dimension L x H x D		in. (mm)	32 3/8 × 21 11/16 × 13 7/8 (822 × 550 × 352)	37 15/16 × 26 × 15 13/16 (964 × 660 × 402)	40 1/8 × 32 1/2 × 17 5/16 (1020 × 826 × 427)	40 1/8 × 32 1/2 × 17 5/16 (1020 × 826 × 427)	40 1/8 × 32 1/2 × 17 5/16 (1020 × 826 × 427)
Net weight		lb (kg)	78.3 (35.5)	112.5 (51)	145.5 (66)	173.1 (78.5)	174.2 (79)
Operating ambient temperature	Cooling	°C (°F)	-30~48 (-22~118)				
	Heating	°C (°F)	-30~24 (-22~75)				
Connection Piping/Refrigerant							
Pre-charge length		ft. (m)	33 (10)	98 (30)	131 (40)	131 (40)	164 (50)
Additional refrigerant charge		oz/ft. (g/m)	0.2 (20)	0.2 (20)	0.2 (20)	0.2 (20)	0.2 (20)
Liquid pipe outer diameter		in.	1/4	1/4	1/4	1/4	1/4
Gas pipe outer diameter		in.	3/8	3/8	3/8	3/8	3/8
Maximum height difference		ft. (m)	49 (15)	49 (15)	82 (25)	82 (25)	82 (25)
Maximum total length		ft. (m)	131 (40)	197 (60)	262 (80)	262 (80)	328 (100)

*10 year standard warranty. Additional 2 year extended warranty with Wolseley when product is registered and/or proof of installation.